LED BR LAMPS



The Superior Life® BR lamps are an efficient way to light sockets once reserved for traditional lamps. They consume up to 80% less energy, thereby significantly reducing operating costs. The superior life hours of this lamp make it ideal for hard to reach places, reducing maintenance.

- **ECO-FRIENDLY, MERCURY FREE**
- **NO UV OR PROJECTED HEAT**
- **WIDE BEAM ANGLE**

Dimmable LED By incorporating advanced circuitry into our LED products, SUPERIOR LIFE® dimmable LED lamps function with switch dimmers just as normal incandescents do by allowing full linear dimming control.
Recommended LED Dimmer: Item# IP710 (Leviton IP710 – LFZ IllumaTech)

ITEM#	DESCRIPTION	WATTS	DIMM	CCT	LM	LM/W	BEAM	CRI	MOL	VOLTS	BASE	LIFE	TRAD. EQUIV.	CASE
BR20 LAMPS														
91339	LED 7BR20/30K/DIMMABLE V5 - SL® ES®	7	YES	30K	525	75	120°	82	3.7	120	MEDIUM	25K	50W	48
91663	LED 8WBR20/30K/DIMMABLE V6 - SL®	7.5	YES	30K	525	70	120°	80	3.7	120	MEDIUM	15K	50W	48
BR30 LAMPS														
90989	LED 8BR30/30K/DIMMABLE V4 - SL®	8	YES	30K	650	81	--	80	5.3	120	MEDIUM	25K	65W	6
90978	LED 8.5BR30/30K/DIMMABLE V4 - SL® ES®	8.5	YES	30K	750	88	110°	83	5.2	120	MEDIUM	25K	65W	20
91665	LED 9WBR30/27K/DIMMABLE V6 - SL®	8	YES	27K	650	72	120°	80	5.2	120	MEDIUM	15K	65W	24
91666	LED 9WBR30/30K/DIMMABLE V6 - SL®	8	YES	30K	650	72	120°	80	5.2	120	MEDIUM	15K	65W	24
91668	LED 9WBR30/50K/DIMMABLE V6 - SL®	8	YES	50K	650	72	120°	80	5.2	120	MEDIUM	15K	65W	24
91345	LED 9BR30/27K/DIMMABLE V5 - SL® ES®	9	YES	27K	650	72	120°	82	5.3	120	MEDIUM	25K	65W	24
91346	LED 9BR30/30K/DIMMABLE V5 - SL® ES®	9	YES	30K	650	72	120°	82	5.3	120	MEDIUM	25K	65W	24
91344	LED 9BR30/40K/DIMMABLE V5 - SL® ES®	9	YES	40K	650	72	120°	82	5.3	120	MEDIUM	25K	65W	24
91347	LED 9BR30/50K/DIMMABLE V5 - SL® ES®	9	YES	50K	650	72	120°	84	5.3	120	MEDIUM	25K	65W	24
90986	LED 10BR30/30K/GU24/DIMMABLE V4 - SL®	10	YES	30K	685	69	120°	80	5.1	120	GU24	40K	65W	24
90981	LED 13.5BR30/27K/DIMMABLE V4 - SL® ES®	13.5	YES	27K	1100	84	110°	84	5.2	120	MEDIUM	25K	85W	20
BR40 LAMPS														
91350	LED 15BR40/30K/DIMMABLE V5 - SL® ES®	15	YES	30K	1100	73	120°	85	6.3	120	MEDIUM	25K	85W	24
91352	LED 15BR40/40K/DIMMABLE V5 - SL® ES®	15	YES	40K	1100	73	120°	81	6.3	120	MEDIUM	25K	85W	24
91351	LED 15BR40/50K/DIMMABLE V5 - SL® ES®	15	YES	50K	1100	73	120°	83	6.3	120	MEDIUM	25K	85W	24
91778	LED 16WBR40/50K/DIMMABLE V6 - SL®	15.5	YES	50K	1100	71	120°	80	6.3	120	MEDIUM	15K	75W	24
90985	LED 17BR40/50K/DIMMABLE V4 - SL®	17	YES	50K	1400	82	110°	80	6.4	120	MEDIUM	25K	100W	16

Key: *DIMM = Dimmable / SL = Superior Life® / ES = Energy Star® / LM = Lumens / TRAD. EQUIV. = Traditional Equivalent*

NOTE: *Due to multiple input voltage integrated circuits, some items may not be compatible with dimming devices. These items may not be compatible with all electronic transformers. • Energy Star® items are certified at the time of production. Please visit www.energystar.gov for the most recent list of qualified products. • Published lumens on LED products are approximate and may vary slightly.*

ENERGY STAR CERTIFIED 3 YEARS WARRANTY

1989 ESTABLISHED P Q L

PREMIUM QUALITY LIGHTING® • www.PQLighting.com

© 2018 P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, Ca 93065 • 800.323.8107 • Fax: 877.619.7053

GO GREEN

0718